

**AMENDMENTS TO THE CLAIMS:**

Please cancel claims 1, 2, 4-8 and 10-14, without prejudice or disclaimer of their subject matter, and add new claims 15-19, as indicated below. This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

1.-14. (Canceled)

15. (New) An electronic apparatus comprising:

a wireless communication device that executes wireless communication with an external device;

an input device;

selecting means for selecting one of a first communication mode and a second communication mode in accordance with an operation of the input device; and

controlling means for controlling the wireless communication between the wireless communication device and the external device, the controlling means including:

first means for, when the first communication mode is selected, establishing one channel between the wireless communication device and the external device, setting a first communication condition for one-way communication in the apparatus and the external device, the first communication condition indicating that a first compression-encoding scheme is used in the one-way communication, compression-encoding content data by the first compression-encoding scheme, and executing the one-way communication to transmit the content data compression-

encoded by the first compression-encoding scheme, from the wireless communication device to the external device via the one channel; and

second means for, when the second communication mode is selected, establishing two independent channels between the wireless communication device and the external device, the two independent channels including a first channel for transmitting content data from the wireless communication device to the external device and a second channel for transmitting content data from the external device to the wireless communication device, setting a second communication condition for two-way communication in the apparatus and the external device, the second communication condition indicating that a second compression-encoding scheme is used in the two-way communication, compression-encoding content data by the second compression-encoding scheme, and executing the two-way communication to transmit the content data compression-encoded by the second compression-encoding scheme from the wireless communication device to the external device via the first channel and receive content data compression-encoded by the second compression-encoding scheme from the external device via the second channel, the second compression-encoding scheme requiring a lesser amount of arithmetic operations compared to the first compression-encoding scheme.

16. (New) The electronic apparatus according to claim 15, further comprising:  
a display device; and

displaying means for displaying a first icon and a second icon corresponding to the first communication mode and the second communication mode, respectively, on a display screen of the display device,

wherein the selecting means includes means for selecting the first communication mode when the first icon is selected by an operation of the input device, and selecting the second communication mode when the second icon is selected by an operation of the input device.

17. (New) The electronic apparatus according to claim 15, wherein the controlling means includes means for controlling communication between the wireless communication device and the external device such that content data sampled with a first sampling frequency is transmitted from the wireless communication device to the external device when the first communication mode is selected, and content data sampled with a second sampling frequency, which is lower than the first sampling frequency, is transmitted and received between the wireless communication device and the external device when the second communication mode is selected.

18. (New) The electronic apparatus according to claim 15, wherein the external device is a headset including a speaker and a microphone.

19. (New) A computer-readable medium which stores a program for controlling wireless communication between a wireless communication device within a computer and an external device, the program comprising:

causing the computer to select one of a first communication mode and a second communication mode in accordance with an operation of an input device of the computer;

causing the computer to establish one channel for transmitting content data from the wireless communication device and the external device, set a first communication condition for one-way communication in the computer and the external device, the first communication condition indicating that a first compression-encoding scheme is used in the one-way communication, compression-encode content data by the first compression-encoding scheme, and execute the one-way communication to transmit the content data compression-encoded by the first compression-encoding scheme, from the wireless communication device to the external device via the one channel, when the first communication mode is selected; and

causing the computer to establish two independent channels between the wireless communication device and the external device, the two independent channels including a first channel for transmitting content data from the wireless communication device to the external device and a second channel for transmitting content data from the external device to the wireless communication device, set a second communication condition for two-way communication in the computer and the external device, the second communication condition indicating that a second compression-encoding scheme is used in the two-way communication, compression-encode content data by the second compression-encoding scheme, and execute the two-way communication to transmit the content data compression-encoded by the second compression-encoding scheme from the wireless communication device to the external device via the first

channel and receive content data compression-encoded by the second compression-encoding scheme from the external device via the second channel, the second compression-encoding scheme requiring a lesser amount of arithmetic operations compared to the first compression-encoding scheme.